



EA Engineering, Science,
and Technology, Inc., PBC
405 State Hwy 121
Bldg. C, Ste. 100
Lewisville, TX 75067

FIELD BOREHOLE LOG

BOREHOLE NO.: WPA-GW-04

TOTAL DEPTH: 12 ft

PROJECT INFORMATION

PROJECT: Wilcox Oil Company Superfund Site

SITE LOCATION: Bristow, Creek County, Oklahoma

ADDRESS: W. 221st Street S.

LOGGED BY: Jacob Meinerts

PROJECT MANAGER: Pat Appel

DATE DRILLED: 8-12-2020

DRILLING INFORMATION

DRILLING CO.: Mohawk Drilling

DRILLER: Tanner Brantley

RIG TYPE: Geoprobe 6610DT

DRILLING METHOD: Direct Push

SAMPLING METHOD: Plastic liners

BOREHOLE SIZE: 1.75 inch

Water level during drilling

✕ Water level after drilling

DEPTH	SOIL/ROCK SYMBOLS	USCS	SAMPLE DESCRIPTION	PID (ppm)	BORING COMPLETION	WELL DETAILS
-5						
0		SW-SC	SW-SC. 7.5YR 4/4 brown. Loose, non-plastic, dry, fine - very fine grained.			1" Sch.40 PVC Riser 0 to 2'
5		SW-SP	SW-SP. 5YR 5/6 yellowish red. Loose, non-plastic, dry, fine - medium grained.			
		SW-SP	SW-SP. 5YR 5/6 yellowish red. Loose, non-plastic, wet, fine - medium grained.			1" Sch.40 PVC Screen 0.010" slots 2' to 12'
10		CL	CL. 7.5YR 5/6 strong brown. Fairly dense, semi plastic, dry.			
		SW-SP	SW-SP. 5YR 5/6 yellowish red. Loose, wet, semi plastic, fine-very fine.			
			CL. 7.5YR 5/6 strong brown. Cohesive, fat, dry, very plastic.			
		CL				TD 12'
15						
20						
25						

NOTES: This log should not be used separately from the original report.

Page 1 of 1